



Protema electric lift PRO100

SPECIFICATIONS:	
Art nr (excluding platform):	8PRO100-1 / 8PRO1005-1
Max. load	100 kg (220 lbs) with centre of load @ max 400 mm (15.75") from mast
Min. lifting height with platform 8522	Floor level, less platform height 30 mm (1.18")
Max. lifting height with platform 8522	8PRO100-1: 1310 mm (51.57") 8PRO1005-1: 1810 mm (71.26")
Stroke	8PRO100-1: 1280 mm (50.39") 8PRO1005-1: 1780 mm (70.08")
Weight of unit	46 kg (102 lbs)
Lifting speed	0,085 m/s
Charging voltage	120/240 V AC 40 W
Battery voltage & capacity	24V DC 17Ah
Lifting capacity/charge	100 x 100 kg x 1m
Total height	8PRO100-1: 1810 mm (71.26") 8PRO1005-1: 2310 mm (90.95")
Wheels	Front Ø60 mm (2.36") rear Ø150 mm (5.91")
Platform size	Art nr 8150: 360x500 mm / Art nr 8151: 600x500 mm



PRO100 with platform 8522 in corrugated aluminium

Protema PRO100 handles weights up to 100 kg (220 lbs).

Available in two different lifting heights.

Powerpack with built-in charger (120/240 V AC).

Adjustable overload protection.

Control system for loading, monitoring and operation of the motor and lift attachments.

Front legs fitted with emergency stop switches that will stop the platform automatically, if activated.

Ball and needle bearing front wheels.

Other attachments available: V-block and rotating platform for roll handling, loading rollers, built-in ladder etc.

CE Cert. 08-SKM-CM-0121

