



## Protema electric lift PRO120

| SPECIFICATIONS:                    |   |
|------------------------------------|---|
| Art nr (excluding platform):       | PRO120S/ PRO120M/ PRO120L   |
| Max. load                          | 120 kg / 265 lbs with centre of load @ 250 mm from mast                             |
| Min. lifting height with platform  | Floor/pallet level  |
| Max. lifting height, floor-/pallet | S: 875/985 mm M: 1425/1535 mm L: 1975/2085 mm                                       |
| Min. lifting height with boom:     | 310 mm  |
| Max. lifting height with boom:     | SH: 1155 ME: 1705 LO: 2255 (mm)   |
| (art nr 8116A)                     |   |
| Stroke                             | SH=845 ME=1395 LO=1945 (mm)   |
| Weight of unit                     | appr 67 kg  |
| Lifting speed - high/low           | 0,1 / 0,04 m/s  |
| Charging voltage                   | 120/240V AC 55W   |
| Battery voltage & capacity         | 24V DC 17Ah   |
| Lifting capacity/charge            | 120kg 1m = 120 times  |
| Total height                       | S=1440 M=1990 L=2540 (mm)   |
| Wheels                             | Lowbuilt: front Ø60 mm, rear Ø125 mm<br>Straight (optional): front and rear Ø125 mm |
| Platform size                      | Art nr 8150: 360x500 mm / Art nr 8151: 600x500 mm                                   |



**(Ladder and platform not included.)**

The Protema 120 handles weights up to 120 kg (265 lbs) and can be supplied in three different lifting heights: Short, Medium and Long (see photo).

Ball and needlebearing front wheels, rear wheels with directional brake.

Powerpac with built-in charger (120/240VAC).

Adjustable overload protection. Duplex chain safety feature. Front legs fitted with emergency stop switches that will stop the platform automatically, if activated.

Control system for loading, monitoring and operation of the motor and lift attachments.

Removable finger-tip control, two lifting speeds.

Platforms art nr 8150 and 8151 available in three versions,  
A: HD polyethylene,  
B: Corrugated aluminium and  
C: Stainless steel.

Other attachments available: foldup platform with forks, adjustable forks, boom, V-block and rotating platform, loading rollers, built-in ladder, coregripper etc.

CE Cert. 08-SKM-CM-0121

