



Protema electric lift PRO150

SPECIFICATIONS:	
Art nr excluding platform	PRO150SH/ PRO150ME
Max. load	150 kg / 331 lbs
Min. lifting height with platform	Floor/pallet level
Max. lifting height, floor-/pallet	SH: 875/985 ME: 1425/1535 (mm)
Min. lifting height with boom Max. lifting height with boom: (art nr 8116A)	310 mm SH: 1145 ME: 1705 (mm)
Min. lifting height with coregripper (art nr 8191) Max. lifting height with coregripper (art nr 8191)	SH/ ME: 109 mm SH: 954 ME: 1504 (mm)
Stroke	SH=845 ME=1395 (mm)
Weight of unit	Appr 67 kg
Lifting speed - high/low	0,08 / 0,048 m/s
Charging voltage	120/240 V AC 40 W
Battery voltage & capacity	24 V DC 17Ah
Lifting capacity/charge	150 kg 1m = 120 times
Total height	SH=1440 ME=1990 (mm)
Wheels	Front wheels fixed Ø80 mm, rear Ø125 mm
Platform size	Art nr 8150: 360x500 mm / Art nr 8151: 600x500 mm



The Protema 150 handles weights up to 150 kg (331 lbs) and can be supplied in two different lifting heights: SHort and MEdium.

Ball and needle bearing fixed front wheels, rear wheels with directional brake.

Powerpac with built-in charger (120/240 V AC).

Adjustable overload protection. Duplex chain safety feature. Front legs fitted with emergency stop switches that will stop the platform automatically, if activated.

Control system for loading, monitoring and operation of the motor and lift attachments.

Removable finger-tip control, two lifting speeds.

Platforms art nr 8150 and 8151 available in three versions,

- A: HD polyethylene,
- B: Corrugated aluminium and
- C: Stainless steel.

Other attachments available: foldup platform with forks, adjustable forks, boom, V-block and rotating platform, loading rollers, built-in ladder etc.

CE Cert. 08-SKM-CM-0121

